

THERMOCOUPLE THERMOMETERS

IP52
WATERPROOF

- Unit: °F/°C
- Support thermocouple type K/J/T
- MAX/MIN/AVG mode
- Temperature upper and lower limit alarm function
- Graphical display
- Multi-point calibration function
- Display backlight
- Data hold function
- Battery level display
- Automatic power off

K-type thermocouple
(included)



0326-CT31

SPECIFICATION

Part No.	0326-CT31	0326-CT32
Channel number	1	2
Weight	.52lb	.55lb
Thermocouple type	K/J/T	
Temperature range	type K	-328°F~2498°F
	type J	-328°F~2192°F
	type T	-328°F~752°F
Temperature accuracy*	$\pm(.3\% \cdot t + .72)^\circ\text{F}$	
Temperature resolution	.02°F	
Sampling rate	2 times/sec	
Display	dot matrix LCD display with backlight	
Operation temperature	14°F~122°F (non-condensing)	
Storage temperature	-4°F~140°F (without battery)	
Power supply	3×AAA alkaline batteries	
Dimension	6.85×2.87×1.57"	

*Temperature accuracy does not include thermocouple error

SPECIFICATION OF K-TYPE THERMOCOUPLE*

Code	Range	Accuracy	Length
0326-K01	-40°F~572°F	$\pm 2.7^\circ\text{F}$	59.0"

*Other types, temperature range and length of thermocouples can be customized

STANDARD DELIVERY

Main unit	1 pc
Battery (AAA)	3 pcs
K-type thermocouple (0326-K01)*	1/2 pcs

*Number of thermocouples is corresponding to the number of channels