

PEN-TYPE CONDUCTIVITY TESTER (BASIC TYPE)

PART No. 0416-EB01

- Suitable for water quality testing, aquaculture, food processing, scientific research, etc.
- Mini design with an electrode diameter of 0.39"
- Manual temperature compensation
- With reading stabilization reminder function
- Replaceable electrodes
- Low voltage alarm
- CR2032 battery, automatic power off
- Probe protection level: IP54



SPECIFICATION

Measuring range	(0~99.9)μS/cm, (100~999)μS/cm, (1.00~9.99) mS/cm, (10.00~99.99)mS/cm, (100~199.9)mS/cm
Resolution	0.01μS/cm, 0.1μS/cm, 1μS/cm, 0.01mS/cm
Accuracy	±1.5%FS
Temperature compensation range	32.0~211.8°F (manual)
Calibration mode	1 point (automatic recognition), electrode constant calibration
Standard solution	1413μS/cm
Power supply	CR2032 battery
Dimension (L×W×H)	1.97×7.40×0.67"
Weight	0.13lb

STANDARD DELIVERY

Main unit	1pc
Conductivity electrode (0416-EB01-E)	1pc
Calibration powder (0416-EB01-S) *	2pcs

* dissolve in distilled water to 50mL