

WATER TEST PRESSURE GAUGES

PART NO. 5210-□□□

- Plastic case, plastic window, brass connection
brass bourdon tube, with memory pointer
- Used for water test



5210-C1D2R3

Process connection

C1	1/4BSP (2" DIA, 2.5" DIA)
C2	1/4ZG (2" DIA, 2.5" DIA)
C3	1/4NPT (2" DIA, 2.5" DIA)

Dial size

D1	2" DIA
D2	2.5" DIA

Pressure range


R1	(0~7bar/0~100psi)
R2	(0~11bar/0~160psi)
R3	(0~14bar/0~200psi)
R4	(0~20bar/0~300psi)

PLASTIC CASE

PLASTIC WINDOW

BRASS
CONNECTION

BRASS
BOURDON TUBE



Part No. example:

5210-C1D2R3	C1 -connection thread 1/4BSP
	D2 -dial size 2.5" DIA
	R3 -pressure range (0~14bar/0~200psi)

SPECIFICATION

Accuracy class	CL 2.5 for 50mm (2"); CL 1.6 for 63mm (2.5")
End connection	with 3/4" female thread copper alloy swivel connection
Ambient temperature	-20°C~60°C (-4°F~140°F)
Medium temperature	≤60°C (140°F)