

PROFILE PROJECTORS(BASIC TYPE)




ISP-D150A

OPTIONAL ACCESSORIES



lens



overlay chart (protractor with 1° graduation, radius with 1mm/.039" increment)



swivel center support



V-block



rotary table



50mm/1.97" reading scale (check magnification accuracy)



300mm/11.81" calibration scale (check magnification accuracy together with 50mm reading scale or calibrate measuring accuracy)



demo sample



printer

SPECIFICATION

Part No.		ISP-D150A	ISP-D150B	ISP-D200A	ISP-D200B	ISP-D250A	ISP-D250B
Projector screen		diameter: 12" DIA					
		rotation range: 0°~360°, resolution: 1" or 0.05°					
		reference lines: cross-hairs					
Lens	magnification	10X (included)	20X (optional)	50X (optional)	100X (optional)		
	view field	1.18" DIA	.59" DIA	.24" DIA	.12" DIA		
	working distance	3.06"	1.74"	1.51"	1.00"		
Max. workpiece height		3.54"	3.54"	3.54"	3.54"		
Magnification accuracy		±0.08%					
Image		erect image	inverted image	erect image	inverted image	erect image	inverted image
Stage	metal stage size	13.39×5.98"		15.91×8.98"		15.94×11.02"	
	glass stage size	7.72×3.78"		10.24×6.30"		12.05×7.72"	
	X-Y stage travel	range: 5.91×1.97"		range: 7.87×3.94"		range: 9.84×5.91"	
		resolution: .00002"					
	accuracy: (157.5+13.3L)µin L is the measuring length in inch						
	Z (focus) travel range	3.54"					
	max. load capacity	8.82lb					
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable					
		surface illumination: 24V/150W halogen lamp					
Data processing unit	display	X-Y stage travel, screen rotation					
	output	RS232C					
	function	measure coordinate of point					
		measure coordinate of line					
		measure center coordinate, radius of circle with three points					
		measure distance between two objects					
		measure angle with four points or two lines					
coordinate adjustment and compensation							
		for some special measurments					
advanced function		programming for batch measurements					
Power supply		110/220V, 50/60Hz					
Dimension (W×D×H)		30.31×21.65×43.31"		30.31×21.65×43.31"		30.71×30.71×43.31"	
Weight		276lb		298lb		320lb	

STANDARD DELIVERY

Main unit	1 pc
10X lens with half-reflection mirror and oblique illuminator mirror	1 pc
Foot-switch	1 pc
Overlay chart clip	4 pcs
Anti-dust cover	1 pc

OPTIONAL ACCESSORY

20X lens with half-reflection mirror and oblique illuminator mirror	ISP-D150-LENS20X
50X lens with half-reflection mirror	ISP-D150-LENS50X
100X lens with half-reflection mirror	ISP-D150-LENS100X
Overlay chart	ISP-D150-CHART
Swivel center support	ISP-D150-SUPPORT
V-block with clamp	ISP-D150-VBLOCK

Rotary table	ISP-D150-TABLE
50mm reading scale	ISP-D150-SCALE50
300mm calibration scale	ISP-D150-RULE
Demo sample	ISP-D150-DEMO
Printer	ISP-D150-PRINTER