

# AUTOMATIC DENSITY METER CODE MDY-MD30

DATA  
OUTPUT

- According to GB/T 29617, GB/T 2013, ISO 12185, ASTM D4052, ASTM D5002, ASTM D3505
- Rapid measurement of liquids such as sugar solutions, fruit juices, alcohols, oils, food additives, metalworking cleaners, etc.
- .0005~.0008 gal of sample is needed each time
- Built-in Peltier temperature control device for more accurate measurements
- Dry air and distilled water can be used for daily calibration
- Compatible with automatic sampling and manual sampling
- Rapid pre-test mode and precision mode
- Data can be saved and reports can be exported



manual sampling



automatic sampling



drying barrel (included)

## SPECIFICATION

Density range	0.0000g/cm <sup>3</sup> ~3.0000g/cm <sup>3</sup>
Measurement method	density g/cm <sup>3</sup> , density kg/m <sup>3</sup> , specific gravity of water
Density resolution	0.0001g/cm <sup>3</sup>
Density accuracy	±0.0005g/cm <sup>3</sup>
Density repeatability	≤0.0002g/cm <sup>3</sup>
Temperature resolution	.02°F
Temperature control range	41°F~122°F
Temperature control precision	±.09°F
Temperature control accuracy	±.2°F
Observation	high definition camera/video observation
Data storage	128G
Display	10.1 inch color LCD touch screen
Power supply	100V~240V, 50Hz~60Hz
Dimension	17.3×13.8×8.5"
Weight	19.8lb

## STANDARD DELIVERY

Main unit	1pc
Power adapter	1pc
PP syringe (MDY-MD30-ZSQ1)	3pcs
Drying barrel	1pc
Waste liquid bottle	1pc
Silicone tube connector	1set
Silicone tube	1pc
Dust cover	1pc

## OPTIONAL ACCESSORY

Stylus printer	MDY-MD30-PRINTER-A
Thermal printer	MDY-MD30-PRINTER-B
PTFE syringe	MDY-MD30-ZSQ2
Glass syringe	MDY-MD30-ZSQ3