

MANUAL PRECISION CUTTING MACHINE PART NO. MLP-PCM100-U





coolant (optional)

cutting blade (optional)



diamond blade (optional)

- Equipped with a high-torque DC motor and stepless speed control system, boasting strong power and high efficiency
- The rotation speed is digitally displayed for simple operation
- With a magnetic safety switch, the motor automatically stops when the protective cover is opened, ensuring safety performance
- Integrally formed high-strength composite material shell, anti-corrosive and rust-proof
- Panoramic transparent observation window, facilitating the observation of the sample cutting process
- With circulating cooling water tank, lightweight in volume

SPECIFICATION

| Maximum cutting diameter | 1.57"DIA |
|--------------------------|-------------------------|
| Maximum travel | 7.48" |
| Diamond blade | 7.87"DIA×0.031"×0.5"DIA |
| Cutting method | manual cutting, Y-axis |
| Rotation speed | 500~3000r/min |
| Table dimension | 14.48×16.69" |
| Motor power | 600W |
| Power supply | 110V, 60Hz |
| Demension (L×W×H) | 21.65×18.70×14.17" |
| Weight | 77.16 lb |

STANDARD DELIVERY

| Main unit | 1 pc |
|---------------|--------------|
| Diamond blade | 1 pc |
| Fixed fixture | 1 set |
| Coolant | 1 barrel, 2L |
| Tool package | 1 set |

OPTIONAL DELIVERY

| Coolant | MLP-OL2 |
|---------------|-----------------|
| Cutting blade | MLP-10R series* |
| Diamond blade | MLP-DQ series* |

*Select the cutting blade with an inner hole of 0.5"DIA and a diameter not exceeding 9.05"